# OPT MED AURORA® IQ

Handheld fundus camera





Autofocus and autoexposure




New high contrast optical design



50 degrees field of view with non-myd operation




Cloud connectivity to optional Al service





Can be mounted to a slit lamp





#### **Image quality**

- 50 degrees field of view combined with nonmydriatic operation allow a detailed examination and ease of use in various use cases.
- New high contrast optical design helps to detect small early phase retinal changes.

#### **Intelligent features**

- Autofocus and autoexposure allow quick usage of the camera without any setting modifications in various use cases.
- Integrated image quality analysis guides first time users to acquire successful images and therefore minimizes training time.
- Pin code protection can be used for ensuring data safety.

### Connectivity

- WLAN and USB connections for image transfer and various ways of handling image data are supported by the camera.
- Integrated Cloud connection allows sending images to an optional AI service for image analysis.

## Technical specification

TYPE Non-mydriatic digital fundus camera

FIELD OF VIEW 50 degrees (total FOV 50x40)

**CAMERA SENSOR RESOLUTION** 5 Mpix

**OPTICAL RESOLUTION** > 60 lp/mm (ISO10940:2009)

**FIXATION TARGETS** 9 internal fixation targets for peripheral imaging (total FOV up to 80 x 60 degrees)

FOCUS RANGE Autofocus, -20D to +20D

MINIMUM PUPIL SIZE 3.1 mm

IMAGE FORMAT JPEG

VIDEO FORMAT MPEG-4

DISPLAY TFT-LCD: 4", 800x480

MEMORY 8GB

**BATTERY** Rechargeable 3.63V/2600mAh Li-ion Battery

**CONNECTIVITY** WLAN, USB

TYPE OF PHOTOGRAPHY Color, Red-free, IR

**DIMENSIONS AND WEIGHT:** 

**Aurora camera** 122(w) x 202(h) x 98 (l) mm, 526g

**Aurora retinal module** 68 (w) x 74 (h) x 160 (l) mm, 327g

**Aurora anterior module** 71 (w) x 80 (h) x 79 (l) mm, 105g

**WARRANTY** 2 years excluding batteries









